



Technical Data Sheet

Oil Based Wood Stain

Product Features

Oil-Based Wood Stain uses high-quality oils, resins, and pigments to give a classic look that accentuates natural grain variation within wood.

Recommended Uses

Interior raw wood surfaces such as cabinets, trim, doors, and furniture.

Complies w/ the following air quality regulations:

Canada. Check local regulations for United States

Application Conditions: Recommended 70°F and 50% humidity, out of direct sunlight, with good air movement. Variations in conditions and application technique can significantly affect dry times and coverage.

Surface Prep: Ensure the surface is clean of contaminants and dust. Variations in wood species, prep procedures, and application procedures can significantly affect color. Always test for color before staining your project.

Raw Wood: On hard woods such as Maple, Birch and Oak, sand no finer than 150 grit. On soft woods such as Pine, Alder and Cherry sand no finer than 180 grit.

Pre-finished Wood: Not recommended

Other Substrates: Not recommended

Application Tips: Apply stain using a rag, bristle brush, foam brush or paint pad applicator and wipe of excess with a clean cloth. If a darker color is desired, allow the first coat to dry completely and then a 2nd coat can be applied in the same manor. Use Pre-Stain Natural for more consistent color on blotchy woods.

System Recommendations: Finish with 3 coats of any GF topcoat.

Storage & Shelf Life: Above 50°F and below 80°F, out of direct sunlight, tightly sealed. Minimize oxygen exposure to prevent drying in the can. Finish preservers such as Bloxygen can help. Best if used within one year of purchase. Unopened and properly stored finish can conservatively last up to 5 years.

Disposal: Always dispose of any leftover coatings in accordance with local laws. Do not pour down the drain. Dispose of any rags and brushes in a fireproof container to prevent spontaneous combustion.

The information and recommendations on this sheet are based upon information gathered at the time of publication and do not act as a safety data sheet. For complete safety and product data, consult the product labels and visit www.generalfinishes.com for complete SDS sheets.

Published March 2020 by General Finishes Corp. East Troy, Wi.

Product Type: Oil-based pigmented stain

Colors Available: 14 colors plus Pre-Satin Natural

Tintable?: Yes

Volume Solids: 28% - 38% (varies by color)

Weight Solids: 37% - 51% (varies by color)

Rec. Film Thickness: N/A

Coverage: Up to 800 sq. ft. per gallon

Viscosity: Thin

Application: Rag, brush, pad applicator

Brush: Natural bristle or foam

Roll: Short nap or foam

HVLP: Not recommended

Air-Assist Airless: Not recommended

Airless: Not recommended

Dry Time (touch): 8+ hours

Dry Time (recoat): 24+ hours

Cure Time: N/A

Thin With: Pre-Stain Natural

Clean Hands w/: Mineral spirits, waterless hand cleaner

Clean Equipment w/: Mineral spirits

Sizes Available: Half-Pints, Quarts

VOC: All colors under 550 g/L