

# SAFETY DATA SHEET

## GF Oil Stain Mocha



### Section 1. Identification

**GHS product identifier** : GF Oil Stain Mocha  
**Product code** : Not available.  
**Other means of identification** : Not available.  
**Product type** : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Oil-based stain.

**Supplier's details** : General Finishes  
 2462 Corporate Circle  
 East Troy, WI 53120  
 U.S.A.  
 Phone no.: 262-642-4545  
 Toll free no.: 1-800-783-6050  
 Fax no.: 262-642-4707  
 Web: GeneralFinishes.com

**Emergency telephone number (with hours of operation)** : CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887 (24/7)

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
 SKIN SENSITIZATION - Category 1  
 GERM CELL MUTAGENICITY - Category 1  
 CARCINOGENICITY - Category 1A  
 TOXIC TO REPRODUCTION (Fertility) - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1  
 ASPIRATION HAZARD - Category 1  
 AQUATIC HAZARD (ACUTE) - Category 3  
 AQUATIC HAZARD (LONG-TERM) - Category 3

#### GHS label elements

##### Hazard pictograms



**Signal word** : Danger



## Section 2. Hazards identification

- Hazard statements**
- : H226 - Flammable liquid and vapor.
  - H319 - Causes serious eye irritation.
  - H317 - May cause an allergic skin reaction.
  - H340 - May cause genetic defects.
  - H350 - May cause cancer.
  - H361 - Suspected of damaging fertility.
  - H304 - May be fatal if swallowed and enters airways.
  - H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS))
  - H412 - Harmful to aquatic life with long lasting effects.

### Precautionary statements

#### **Prevention**

- : P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P233 - Keep container tightly closed.
- P273 - Avoid release to the environment.
- P260 - Do not breathe vapor.
- P270 - Do not eat, drink or smoke when using this product.
- P264 - Wash hands thoroughly after handling.
- P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.

#### **Response**

- : P314 - Get medical attention if you feel unwell.
- P308 + P313 - IF exposed or concerned: Get medical attention.
- P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.
- P333 + P313 - If skin irritation or rash occurs: Get medical attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical attention.

#### **Storage**

- : P405 - Store locked up.
- P403 - Store in a well-ventilated place.
- P235 - Keep cool.

#### **Disposal**

- : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### **Hazards not otherwise classified**

- : None known.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

## Section 3. Composition/information on ingredients

| Ingredient name                             | %         | CAS number |
|---|-----------|------------|
| Solvent naphtha (petroleum), medium aliph.  | ≥25 - ≤50 | 64742-88-7 |
| Stoddard solvent                            | ≥10 - ≤25 | 8052-41-3  |
| Umber                                       | ≥5 - ≤10  | 12713-03-0 |
| Distillates (petroleum), hydrotreated light | ≥5 - ≤10  | 64742-47-8 |
| Carbon black, respirable powder             | ≥1 - ≤3   | 1333-86-4  |
| 2-Butanone oxime                            | ≤0.3      | 96-29-7    |
| Ethylbenzene                                | ≤0.3      | 100-41-4   |
| Crystalline silica, respirable powder       | ≤0.3      | 14808-60-7 |
| Cobalt bis(2-ethylhexanoate)                | ≤0.3      | 136-52-7   |

The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

## Section 4. First aid measures

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.
- Unsuitable extinguishing media** : Do not use water jet or water-based fire extinguishers.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

## Section 5. Fire-fighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

| Ingredient name                             | Exposure limits   |
|---|---|
| Solvent naphtha (petroleum), medium aliph.  | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 100 ppm 8 hours.<br>TWA: 400 mg/m <sup>3</sup> 8 hours.  |
| Stoddard solvent                            | <b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 100 ppm 8 hours.<br>TWA: 525 mg/m <sup>3</sup> 8 hours.<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 350 mg/m <sup>3</sup> 10 hours.<br>CEIL: 1800 mg/m <sup>3</sup> 15 minutes.   |
| Umber                                       | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 500 ppm 8 hours.<br>TWA: 2900 mg/m <sup>3</sup> 8 hours.<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 1 mg/m <sup>3</sup> , (as Mn) 10 hours. Form: Fertilizer and/or industrial use.<br>STEL: 3 mg/m <sup>3</sup> , (as Mn) 15 minutes. Form: Fertilizer and/or industrial use.<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 0.1 mg/m <sup>3</sup> , (as Mn) 8 hours. Form: Inhalable fraction<br>TWA: 0.02 mg/m <sup>3</sup> , (as Mn) 8 hours. Form: Respirable fraction |
| Distillates (petroleum), hydrotreated light | <b>OSHA PEL (United States, 5/2018).</b><br>CEIL: 5 mg/m <sup>3</sup> , (as Mn)   |
| Carbon black, respirable powder             | <b>ACGIH TLV (United States, 3/2018). Absorbed through skin.</b><br>TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapor) 8 hours.<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 3.5 mg/m <sup>3</sup> 10 hours.<br>TWA: 0.1 mg of PAHs/cm <sup>3</sup> 10 hours.<br><b>OSHA PEL (United States, 5/2018).</b><br>TWA: 3.5 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction   |
| 2-Butanone oxime                            | <b>AIHA WEEL (United States, 7/2018). Skin sensitizer.</b><br>TWA: 10 ppm 8 hours.  |
| Ethylbenzene                                | <b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 20 ppm 8 hours.<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 100 ppm 10 hours.<br>TWA: 435 mg/m <sup>3</sup> 10 hours.<br>STEL: 125 ppm 15 minutes.<br>STEL: 545 mg/m <sup>3</sup> 15 minutes.<br><b>OSHA PEL (United States, 5/2018).</b><br>TWA: 100 ppm 8 hours.<br>TWA: 435 mg/m <sup>3</sup> 8 hours.   |
| Crystalline silica, respirable powder       | <b>OSHA PEL Z3 (United States, 6/2016).</b><br>TWA: 250 mppcf / (%SiO <sub>2</sub> +5) 8 hours. Form: Respirable<br>TWA: 10 mg/m <sup>3</sup> / (%SiO <sub>2</sub> +2) 8 hours. Form: Respirable<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 0.05 mg/m <sup>3</sup> 10 hours. Form: Respirable dust<br><b>OSHA PEL (United States, 5/2018).</b><br>TWA: 50 µg/m <sup>3</sup> 8 hours. Form: Respirable dust<br><b>ACGIH TLV (United States, 3/2018).</b><br>TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction         |
| Cobalt bis(2-ethylhexanoate)                | <b>ACGIH TLV (United States, 3/2018).</b>   |



## Section 8. Exposure controls/personal protection

TWA: 0.02 mg/m<sup>3</sup>, (as Co) 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Brown.
- Odor** : Slight.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.

## Section 9. Physical and chemical properties

|   |  |
|---|--|
| <b>Flash point</b>                                  | : Closed cup: 37.8 to 61°C (100 to 141.8°F)      |
| <b>Evaporation rate</b>                             | : Not available.                                 |
| <b>Flammability (solid, gas)</b>                    | : Not available.                                 |
| <b>Lower and upper explosive (flammable) limits</b> | : Not available.                                 |
| <b>Vapor pressure</b>                               | : Not available.                                 |
| <b>Vapor density</b>                                | : Not available.                                 |
| <b>Relative density</b>                             | : 0.921  |
| <b>Solubility</b>                                   | : Soluble in mineral spirits.                    |
| <b>Partition coefficient: n-octanol/water</b>       | : Not available.                                 |
| <b>Auto-ignition temperature</b>                    | : Not available.                                 |
| <b>Decomposition temperature</b>                    | : Not available.                                 |
| <b>Viscosity</b>                                    | : Dynamic (room temperature): 100 mPa·s (100 cP) |
| <b>VOC content</b>                                  | : 487.3 g/L                                      |
| <b>Flow time (ISO 2431)</b>                         | : Not available.                                 |

## Section 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.  |
| <b>Chemical stability</b>                 | : The product is stable.  |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| <b>Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |
| <b>Incompatible materials</b>             | : Reactive or incompatible with the following materials: oxidizing materials.   |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name         | Result      | Species | Dose         | Exposure |
|---------------------------------|-------------|---------|--------------|----------|
| Carbon black, respirable powder | LD50 Oral   | Rat     | >15400 mg/kg | -        |
| 2-Butanone oxime                | LD50 Oral   | Rat     | 930 mg/kg    | -        |
| Ethylbenzene                    | LD50 Dermal | Rabbit  | >5000 mg/kg  | -        |
|                                 | LD50 Oral   | Rat     | 3500 mg/kg   | -        |
| Cobalt bis(2-ethylhexanoate)    | LD50 Dermal | Rabbit  | >5 g/kg      | -        |
|                                 | LD50 Oral   | Rat     | 1.22 g/kg    | -        |

#### Irritation/Corrosion



## Section 11. Toxicological information

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| Stoddard solvent        | Eyes - Mild irritant     | Human   | -     | 100 ppm         | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| 2-Butanone oxime        | Eyes - Severe irritant   | Rabbit  | -     | 100 µl          | -           |
| Ethylbenzene            | Eyes - Severe irritant   | Rabbit  | -     | 500 mg          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 mg  | -           |

### Sensitization

There is no data available.

### Mutagenicity

There is no data available.

### Carcinogenicity

#### Classification

| Product/ingredient name               | OSHA | IARC | NTP  |
|---------------------------------------|------|------|--|
| Carbon black, respirable powder       | -    | 2B   | -  |
| Ethylbenzene                          | -    | 2B   | -  |
| Crystalline silica, respirable powder | -    | 1    | Known to be a human carcinogen.                  |
| Cobalt bis(2-ethylhexanoate)          | -    | 2B   | Reasonably anticipated to be a human carcinogen. |

### Reproductive toxicity

There is no data available.

### Teratogenicity

There is no data available.

### Specific target organ toxicity (single exposure)

There is no data available.

### Specific target organ toxicity (repeated exposure)

| Name                                       | Category   | Target organs                |
|--|------------|------------------------------|
| Solvent naphtha (petroleum), medium aliph. | Category 1 | central nervous system (CNS) |
| Stoddard solvent                           | Category 1 | central nervous system (CNS) |
| Ethylbenzene                               | Category 2 | hearing organs               |
| Crystalline silica, respirable powder      | Category 1 | respiratory tract            |

### Aspiration hazard

| Name  | Result                         |
|---|--------------------------------|
| Solvent naphtha (petroleum), medium aliph.  | ASPIRATION HAZARD - Category 1 |
| Stoddard solvent                            | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), hydrotreated light | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene                                | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Dermal contact. Eye contact. Inhalation. Ingestion.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion** : May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

#### Potential chronic health effects

- General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : May cause genetic defects.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

### Numerical measures of toxicity

#### Acute toxicity estimates

There is no data available.

## Section 12. Ecological information

### Toxicity

| Product/ingredient name                     | Result                             | Species                             | Exposure |
|---|------------------------------------|-------------------------------------|----------|
| Distillates (petroleum), hydrotreated light | Acute LC50 2200 µg/L Fresh water   | Fish - Lepomis macrochirus          | 4 days   |
| Carbon black, respirable powder             | Acute EC50 37.563 mg/L Fresh water | Daphnia - Daphnia magna - Neonate   | 48 hours |
| 2-Butanone oxime                            | Acute LC50 843000 µg/L Fresh water | Fish - Pimephales promelas          | 96 hours |
| Ethylbenzene                                | Acute LC50 13.3 mg/L Marine water  | Crustaceans - Artemia sp. - Nauplii | 48 hours |
|   | Acute LC50 13.9 mg/L Fresh water   | Daphnia - Daphnia magna - Neonate   | 48 hours |

### Persistence and degradability

## Section 12. Ecological information

There is no data available.

### Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF        | Potential |
|------------------------------|--------------------|------------|-----------|
| Stoddard solvent             | 3.16 to 7.06       | -          | high      |
| 2-Butanone oxime             | 0.63               | 2.5 to 5.8 | low       |
| Ethylbenzene                 | 3.6                | -          | low       |
| Cobalt bis(2-ethylhexanoate) | -                  | 15600      | high      |

### Mobility in soil




Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                            | DOT Classification   | IMDG   | IATA   |
|----------------------------|--|--|--|
| UN number                  | UN1263   | UN1263   | UN1263   |
| UN proper shipping name    | PAINT  | PAINT  | PAINT  |
| Transport hazard class(es) | 3<br> | 3<br> | 3<br> |
| Packing group              | III  | III  | III  |
| Environmental hazards      | No.  | No.  | No.  |

AERG : 128

DOT-RQ Details : Xylene

100 lbs / 45.4 kg [13.946 gal / 52.791 L]

### Additional information

## Section 14. Transport information

- DOT Classification** : This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity.  
**Reportable quantity** 14699.4 lbs / 6673.5 kg [1914.2 gal / 7246 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

- U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 307:** Ethylbenzene; Naphthalene  
**Clean Water Act (CWA) 311:** Xylene; Ethylbenzene; Naphthalene
- Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor Chemicals)** : Not listed
- DEA List II Chemicals (Essential Chemicals)** : Not listed
- SARA 302/304**  
No products were found.
- SARA 304 RQ** : Not applicable.
- SARA 311/312 Classification** : FLAMMABLE LIQUIDS - Category 3  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
GERM CELL MUTAGENICITY - Category 1  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION (Fertility) - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1  
ASPIRATION HAZARD - Category 1
- Composition/information on ingredients**

## Section 15. Regulatory information

| Name  | Classification  |
|---|---|
| Solvent naphtha (petroleum), medium aliph.  | FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1<br>ASPIRATION HAZARD - Category 1  |
| Stoddard solvent                            | FLAMMABLE LIQUIDS - Category 3<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A<br>GERM CELL MUTAGENICITY - Category 1B<br>CARCINOGENICITY - Category 1B<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1<br>ASPIRATION HAZARD - Category 1   |
| Distillates (petroleum), hydrotreated light | FLAMMABLE LIQUIDS - Category 3<br>ASPIRATION HAZARD - Category 1  |
| Carbon black, respirable powder             | CARCINOGENICITY - Category 2  |
| 2-Butanone oxime                            | FLAMMABLE LIQUIDS - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1<br>SKIN SENSITIZATION - Category 1<br>CARCINOGENICITY - Category 2  |
| Ethylbenzene                                | FLAMMABLE LIQUIDS - Category 2<br>ACUTE TOXICITY (inhalation) - Category 4<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A<br>CARCINOGENICITY - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2<br>ASPIRATION HAZARD - Category 1<br>CARCINOGENICITY - Category 1A<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) (inhalation) - Category 1 |
| Crystalline silica, respirable powder       | ACUTE TOXICITY (oral) - Category 4<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1A<br>CARCINOGENICITY - Category 2  |
| Cobalt bis(2-ethylhexanoate)                | TOXIC TO REPRODUCTION (Fertility) - Category 2  |

### SARA 313


|                                 | Product name  | CAS number                         |
|---------------------------------|---|------------------------------------|
| Form R - Reporting requirements | Umber   | 12713-03-0                         |
|                                 | Ethylbenzene  | 100-41-4                           |
|                                 | Cobalt bis(2-ethylhexanoate)                          | 136-52-7                           |
| Supplier notification           | Umber<br>Ethylbenzene<br>Cobalt bis(2-ethylhexanoate) | 12713-03-0<br>100-41-4<br>136-52-7 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: Stoddard solvent; Carbon black, respirable powder
- New York** : The following components are listed: Ethylbenzene
- New Jersey** : The following components are listed: Stoddard solvent; Ethylbenzene; Carbon black, respirable powder; Crystalline silica, respirable powder; Cobalt bis(2-ethylhexanoate)
- Pennsylvania** : The following components are listed: Stoddard solvent; Ethylbenzene; Umber; Carbon black, respirable powder; Crystalline silica, respirable powder; Cobalt bis(2-ethylhexanoate)

### California Prop. 65

 **WARNING:** This product can expose you to chemicals including Carbon black, respirable powder, Ethylbenzene, Crystalline silica, respirable powder and Naphthalene, which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Section 16. Other information

### Procedure used to derive the classification

| Classification  | Justification  |
|---|--|
| FLAMMABLE LIQUIDS - Category 3<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1<br>GERM CELL MUTAGENICITY - Category 1<br>CARCINOGENICITY - Category 1A<br>TOXIC TO REPRODUCTION (Fertility) - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 1<br>ASPIRATION HAZARD - Category 1<br>AQUATIC HAZARD (ACUTE) - Category 3<br>AQUATIC HAZARD (LONG-TERM) - Category 3 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Expert judgment<br>Calculation method<br>Calculation method |

### History

|                                 |  |
|---------------------------------|--|
| <b>Date of issue mm/dd/yyyy</b> | : 10/30/2019   |
| <b>Date of previous issue</b>   | : Not applicable   |
| <b>Version</b>                  | : 1  |
| <b>Prepared by</b>              | : KMK Regulatory Services Inc.   |
| <b>Key to abbreviations</b>     | : ATE = Acute Toxicity Estimate<br>BCF = Bioconcentration Factor<br>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br>IATA = International Air Transport Association<br>IBC = Intermediate Bulk Container<br>IMDG = International Maritime Dangerous Goods<br>LogPow = logarithm of the octanol/water partition coefficient<br>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)<br>UN = United Nations |

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.